2019 NAVIGATION/MULTIMEDIA Receiver Firmware Update Guide

Introduction

- This document describes the procedure and precautions for upgrading the 2019 NAVIGATION/MULTIMEDIA receiver firmware.
- If an error occurs while you are updating the firmware, the 2019 NAVIGATION/MULTIMEDIA receiver may become unusable. Be sure to read the following procedure and precautions carefully before updating the firmware.

Target Model and Firmware Version

The updater can be used for the firmware versions of the models shown below.

Target models	Target firmware versions → Updated versions
DNX996XR	Ver. 1.8.0009.3700 or earlier → 1.9.0009.3700
DNX9190DABS (Europe)	Ver. 2.0.0009.3800 or earlier → 2.1.0009.3800
DNX9190DABS (Oceania), DNX9190S, DNX9190SM	Ver. 1.8.0009.3900 or earlier → 1.9.0009.3900
DNX7190DABS, DNX5190DABS, DNX576S, DNR476S, DNR4190DABS, DNX419DABS, DNR3190BTS	Ver. 1.8.0009.4000 or earlier → 1.9.0009.4000
DNX696S	Ver. 1.8.0009.4100 or earlier → 1.9.0009.4100
DNR876S	Ver. 1.8.0009.4600 or earlier → 1.9.0009.4600



 For how to check your firmware version, refer to "Checking the Firmware Version".

Work Flow

- Step 1. Download the firmware files, and copy them to USB memory.
- Step 2. Update the firmware. (It takes about 6 minutes.)
- Step 3. Check that the firmware has been updated.

Creating the Update Media

Create the update media on your PC.

- 1. Download the Updates from the Web site.
- 2. Decompress the downloaded file.
- 3. Copy the decompressed file to the top of hierarchy in USB memory.





- USB memory File system: FAT 16/32, NTFS, exFAT
- Do not copy the updater to a device containing audio files. Blank USB memory is highly recommended.
- Update cannot be performed if it is copied inside a folder.
- If the updater file name is changed, update cannot be performed.

Checking the Firmware Version


1. Press the <MENU> button.



2. Touch [SETUP].



- 3. 1 Touch [Special].
 - 2 Touch [Software Information].




4. Check the version.



Updating the Program

- Connect the USB memory.
 The confirmation message appears.
- 2. Touch [Yes] to update starts. (It takes about 6 minutes.)



Caution: The screen may go blank for a few seconds. Do not unplug the USB memory or Power Off the unit during the Update Procedure.

- 3. System Reboot & Software Update Screens
- 4. Once the "Update completed." screen is displayed, remove the USB memory.
- Check that the firmware version is updated, by referring to "Checking the Firmware Version".
 When "1.9.0009.xx00"/"2.1.0009.3800" is displayed, the firmware version is updated successfully.

Precautions

- Update cannot be performed with other media.
- Be sure to park the vehicle in a safe place before updating. Keep the engine running in order to prevent battery from running out.
- Do not turn off the engine or Navigation/Multimedia receiver power while updating. Update cannot be performed correctly and the Navigation/Multimedia receiver may become unusable.